

GOLD STANDARD INSTALLATION

CINDERELLA COMFORT TOILET- PP FLUE

- Over 70% of toilet issues are the direct result of faulty installation.
- Faults caused by a faulty installation are not covered by the 3 year warranty.
- Max 6 metres (straight) ventpipes.
- Ensure the electric connection can be easily disconnected so the toilet can be taken outside for a thorough clean.
- You are allowed to have two 45° bends with maximum 1 metre between them.



600 MM ABOVE THE ROOF

Important! The pipe must be installed vertically above the roof and extend at least 600 mm above the roof surface.

UV-STABILIZED VENT PIPES

Max 6 metres (straight) vent pipes behind the toilet. 45° bends are allowed, then the max length of the pipes is 5 metres. **No leaning pipes allowed.**

BEND W/CONDENSATION CONNECTOR

Better airflow, easier installation and cleaning. The option to connect a condensation trap (*indoors installations only*).

AIR INLET

Allow a good flow of oxygen straight in to the incineration toilet.

THE GOLDEN RULES

One liner, one user, flush after every use. Don't leave a used liner sitting in the pan as urine can leak out after 20 – 30min going on the parts and causing corrosion. Empty the ashpan weekly and steam clean each time. Flush the catalytic converter after every box of liners used or if it is looking dirty sooner than this. This will ensure that the toilet will burn more efficiently and reduce the frequency of servicing. **Thank you!**

We would like to remind you about the importance of following the maintenance instructions for your toilet. Regular maintenance not only ensures optimal performance but also extends the lifetime of your investment. Please refer to your manual provided with your purchase or click the following link: www.ecoash.co.nz/maintenance

Contact us before you make an installation outside of these guidelines.
To activate your warranty email photos of your installation to: sales@ecoash.co.nz

Brian and Leanne Sickler | P: 027 444 8941